



A Tata Steel Enterprise

**NUMBER OF SAB SANDWICH PANELS PRO TYPE AND PACK**

**Per 01-07-2019**

Type	Stacking method	Thickness (mm)	Max. number @	Packheight (incl. packaging)
<b>WALL PANELS</b>				
SAB WB 60.1000 - SAB WB-FA 60.1000	A/A * tot 13,8 m	60	18	1201
SAB WB 60.1000 (EW30) - SAB WB-FA 60.1000	B/B * > 13,8 m	60	18	1201
SAB WB 80.1000 (EW30) - SAB WB-FA 80.1000	A/A * tot 13,8 m	80	13	1161
SAB WB 80.1000 (EW30) - SAB WB-FA 80.1000	B/B * > 13,8 m	80	13	1161
SAB WB 100.1000 (EW30) - SAB WB-FA 100.1000	A/A *	100	10	1121
SAB WB 120.1000 (EW30) - SAB WB-FA 120.1000	A/A *	120	9	1201
SAB-Carrier WB 80.1000	A/A *	80	13	1161
SAB-Carrier WB 100.1000	A/A *	100	10	1121
SAB-Carrier WB 120.1000	A/A *	120	9	1201
SAB-Carrier W 80.1150	A/A * of B/B #	80	13	1161
SAB-Carrier W 100.1150	A/A *	100	10	1121
SAB-Carrier W 120.1150	A/A *	120	9	1201
SAB-Carrier W 150.1150	A/A *	150	7	1171
SAB-Carrier W 95.1020 TL	A/B *	95	11	1166
SAB-Carrier W 135.1020 TL	A/B *	135	7	1066
SAB W 40.1150 - SAB W-FA 40.1150	A/A * of B/B #	40	27	1201
SAB W 60.1150 - SAB W-FA 60.1150	A/A * of B/B #	60	18	1201
SAB W 80.1150 - SAB W-FA 80.1150	A/A * of B/B #	80	13	1161
SAB W 100.1150 - SAB W-FA 100.1150	A/A *	100	10	1121
SAB W 120.1150 (Ei30) - SAB W-FA 120.1150	A/A *	120	9	1201
SAB W 150.1150 (Ei30) - SAB W-FA 150.1150	A/A *	150	7	1171
SAB W 95.1020 TL (Ei15)	A/B *	95	11	1166
SAB W 135.1020 TL (Ei15)	A/B *	135	7	1066
SAB W 100.1000 SL	A/B *	100	12	1137
SAB W 120.1000 SL	A/B *	120	10	1229
<b>ROOFPANELS Nieuwegein</b>				
SAB D 75.1000 TL	A/B #	75	18	1156
SAB D 75.1000 TL	A/A * of B/B #	75	14	1171
SAB D 95.1000 TL	A/B #	95	14	1206
SAB D 95.1000 TL	A/A * of B/B #	95	11	1166
SAB D 115.1000 TL	A/B #	115	10	1096
SAB D 115.1000 TL	A/A * of B/B #	115	9	1156
SAB D 135.1000 TL	A/B #	135	9	1196
SAB D 135.1000 TL	A/A * of B/B #	135	8	1201
<b>ROOFPANELS Geldermalsen (start autumn 2019)</b>				
SAB D 70.1000 TL	A/B #	70	19	1252
SAB D 70.1000 TL	A/A * of B/B #	70	15	1215
SAB D 90.1000 TL	A/B #	90	14	1236
SAB D 90.1000 TL	A/A * of B/B #	90	12	1245
SAB D 110.1000 TL	A/B #	110	11	1240
SAB D 110.1000 TL	A/A * of B/B #	110	9	1155
SAB D 130.1000 TL	A/B #	130	9	1227
SAB D 130.1000 TL	A/A * of B/B #	130	8	1205
SAB D 160.1000 TL	A/B #	160	7	1204
SAB D 160.1000 TL	A/A * of B/B #	160	6	1125
SAB D 83.1000 SL	A/B *	83	16	1181
SAB D 120.1000 SL	A/B *	120	10	1170
SAB D 160.1000 SL	A/B *	160	7	1168

**Total maximum packheight (including packaging) = 1200 mm**

@ Maximum number of panels per package depends on length of the panels, partly because package maximum weight of 2,500 kg should not exceed

\* standard pack stacking

# stacking possible on request

Stand: July 2019