

Product Health & Safety Data Sheet

SAB sandwich panels for Roof and Wall cladding

<p>Product Uses The products are used for Roof & Wall cladding to buildings. To be used in accordance with approved practices and building regulations.</p> <p>Product Identification</p> <ul style="list-style-type: none"> • Wall panels WB and W (FR) • Wall panels Carrier WB and W • Roofing panels D <p>Composition The panels are manufactured with coated Steel outer and inner skins, which are auto-adhesively bonded to a polyisocyanurate (PIR) foam core.</p> <p>Health hazards identification Not applicable.</p> <p>Storage</p> <ul style="list-style-type: none"> • Store in original packing in a location free from any ignition hazard, such as open flames, cutting and welding torches, high surface temperature electric heaters and other forms of direct radiant heat. • Ensure stability of stack and provide adequate aisle space for access between stacks. <p>Handling /installation</p> <ul style="list-style-type: none"> • When handling the panels there is a risk of lacerations of the skin. • The panels are delivered in heavy bundles and can be made in long lengths, injury may occur if lifted incorrectly. • When cutting the product, flying swarf could injure the skin or eyes. Cutting can also produce dust, which may cause irritation if inhaled. • If working using a flame or other ignition hazard near exposed polyisocyanurate core, the product should be protected with a heat resistant material. <p>Fire-fighting measures</p> <ul style="list-style-type: none"> • It is sensible to take precautions against ignition, fire and smoke hazards. In fire situations avoid smoke inhalation and be aware of low visibility. • Suitable media: Water -spray (-fog), foam, CO2 or dry chemical 	<p>Exposure controls/ personal protection</p> <ul style="list-style-type: none"> • Inhalation: Dust is non-hazardous. As with all cutting procedures it is recommended to wear a disposable dust mask (P3). When dust is generated through mechanical cutting in confined spaces, it is recommended that extraction will be used. • Hands: It is recommended to wear gloves with a high cut protection when handling the product. • Eyes: Eye protection is recommended during mechanical cutting. • Skin: Non-sensitising. • Other: the smooth facing used on roof products can be slippery underfoot when wet or other adverse weather conditions. • In a fire, breathing apparatus should be worn. <p>First aid measures:</p> <ul style="list-style-type: none"> • Inhalation: Dust is non-hazardous. Remove the person to fresh air. • Skin: Non-sensitising. • Eyes: Dust particles should be removed by flushing with clean water. • Ingestion: No information available. • Other: Seek medical attention if discomfort persists. <p>Transport To avoid unsafe situations during transport, the product should be adequate secured according European guidelines. Panels are form-stable and can as a minimum be secured with lashings methods.</p> <p>Ecological information The product is inert and stable in water and soil.</p> <p>Disposal considerations Waste product, as well as packaging and protection material, should be disposed of in accordance with local laws and regulations.</p> <p>Manufactured by: SAB-profiel bv / A Tata steel Enterprise Produktieweg 2 NL -3401 MG IJsselstein T +31 30 6879700 info@sabprofiel.nl</p>
--	--