


TECHNICAL DATA SHEET

SAB Sandwich Wall panels FM Approved (WB-FA 60-140)



Thickness	Weight*	U-value	Reaction to fire	Sound insulation
60 mm	10,50 kg/m ²	0,36 W/m ² K	B-s2, d0	26dB
80 mm	11,30 kg/m ²	0,27 W/m ² K	B-s2, d0	26dB
100 mm	12,10 kg/m ²	0,21 W/m ² K	B-s2, d0	26dB
120 mm	12,90 kg/m ²	0,18 W/m ² K	B-s2, d0	26dB
140 mm	13,70 kg/m ²	0,15 W/m ² K	B-s2, d0	26dB

*Outer skin steel 0,50 mm
Inner skin steel 0,40 mm

STEEL GRADE

Yield strength minimum 280 N/mm², zinc layer can be Z, AZ, ZA or ZM.

CORE MATERIAL

Fire safe, CFC-, HCFC- and fibre-free polyisocyanurate foam (PIR) with a closed cell structure.

WIND AND WATER TIGHTNESS

$q_{v,10} = 0,130 \text{ dm}^3/\text{s}$ according EN 12114

Class B according EN 14509

SUSTAINABILITY

Environmentally relevant product information is published on the [SAB-website](https://www.sabprofiel.nl).

QUALITY CONTROLE

Factory production control according EN 14509 and additional voluntary external production control.

SPANS

Depend on wind loads, deflection limitations and safety factors.

See our SAB-brochure for more information.

STANDARDS

FM approved, according 4880 and 4881 without height limitations

Production according ISO 9001, ISO 14001, ISO 45001 and BES 6001

CE-marking and Declaration of Performance according EN 14509

Tolerances according PPA-Europe Quality Regulations

U-value according EN 14509 including impact of the joint

Steel thickness: EN 10143 is used as a basis for the gauge tolerances, applied to the steel core only and excluding zinc layer and organic coating.

IJsselstein, August 2026



European Association for
Panels and Profiles



SAB-profiel bv | Produktieweg 2, NL-3401 MG IJsselstein | Postbus 97, NL-3400 AB IJsselstein

T +31 (0)30 68 79 700 | info@sabprofiel.nl | www.sabprofiel.nl | KvK 30032168

BNP Paribas nr. 22.76.82.548 | BIC: BNPNL2A | IBAN: NL15 BNPA 0227 6825 48

BTW NL001720971B01 | BTW DE164798556 | Steuernummer 116/5963/0134